

OUTDOOR_SPOTLIGHT

RL.IG7054 series

Description

- Color temperature options: 2700K, 3000K, 4000K
- SDCM (Mac Adam Ellipse): ≤ 3
- Color rendering index: Single colors ≥ 80 , RGBW ≥ 70
- Up to 50,000 hours L80 lamp life with LM80 tested LED chip packages
- Beam pattern options: 10°, 25°, 45°, 60°, 120° (Diffuse)
- Luminous efficiency: 35 lm/W – 100 lm/W (depending on LED and CCT)
- Protect eyes and reduced flicker percentage
- Body: Light body adopts high pressure die-casting aluminum. Lampshade adopts high strength toughened glass, resist the impact and friction.
Optional - marine grade sea salt corrosion resistant
- Ambient Humidity: 10% ~ 90%
- Ambient Temperature: -20°C ~ 50°C
- IP67/ IK08
- Surface color: SS316 and Aluminum



Specification

Model	RL.IG7054-R	RL.IG7054-S
Power	2.6W	2.6W
Input Voltage	DC24V/ AC 220 – 240V	DC24V/ AC 220 – 240V
Lumen	120 Lm	120 Lm
Color	2700K/3000K/4000K	2700K/3000K/4000K
Beam Angle	10°, 25°, 45°, 60°, 120° (Diffuse)	
Control Mode	On-Off/ O-10V/ DALI	On-Off/ O-10V/ DALI

To get an order code: RL.IG7054-R-27-10 (Model: RL.IG7054; R - Round ; 27 - CCT 2700K; 10 - Beam angle 10°)